



MODEL	A	B	C	D	E	F	G	Radiating Pipe	Cooling Area (m <sup>2</sup> )	Capacity of tank	Weight (kg)	Flow of pump (L/min)	Water flow (L/min)
HS-0905(OR-60)	465	295	40	89.1	120	3/4"	3/4"	22	0.24	60	8	100	50
HS-0908(OR-100)	540	370	55	114.3	140	3/4"	3/4"	26	0.35	100	12	200	100
HS-1405(OR-150)	580	375	65	139.8	170	1 1/4"	3/4"	42	0.6	150	15	300	150
HS-1408(OR-250)	800	600	65	139.8	170	1 1/4"	3/4"	58	1.2	250	22	300	150
HS-1412(OR-350)	1205	1000	65	139.8	170	1 1/4"	3/4"	58	1.9	350	30	300	150
HS-1712(OR-600)	1225	970	85	165.2	196	2"	1 1/2"	58	1.9	600	40	400	200
HS-1716(OR-800)	1725	1470	85	165.2	196	2"	1 1/2"	58	2.8	800	50	400	200
HS-1720(OR-1000)	2140	1890	85	165.2	196	2"	1 1/2"	58	3.5	1000	60	400	200
HS-1724(OR-1200)	2520	2270	85	165.2	196	2"	1 1/2"	58	4.2	1200	70	400	200