



Pressure Reducing (and Check) Valve

20 to 280 ℓ /min
21MPa



Features


- ① This valve is used when part of the circuit uses pressure that is lower than the main circuit.
- ② Even when pressure changes in the primary main circuit, the reduced secondary pressure is adjusted automatically and maintained at a constant level.
- ③ Connecting a remote control valve to the vent port allows remote control of adjustment pressure.
- ④ The mounting surface of the gasket conforms to the ISO standards shown in the table below.

Specifications

Model No.		Nominal Diameter (Size)	Maximum Working Pressure MPa(kgf/cm ²)	Maximum Flow Rate ℓ /min	Pressure adjustment range MPa(kgf/cm ²)	Weight kg		Gasket Surface Dimensions
Screw Mounting	Gasket Mounting					T Type	G Type	
(C)G-T03-A-21 B-21	(C)G-G03-A-21 B-21	3/8	21{214} IN, OUT, Vent Port	20	0.25 to 1{2.6 to 10.2} 0.3 to 2.5{3.1 to 25.5}	3.3 (3.6)	3.9 (4.2)	ISO 5781-AG-06-2-A
(C)G-T03-1-21 3-21	(C)G-G03-1-21 3-21	3/8		50	0.8 to 7{8.2 to 71.4} 3.5 to 21{35.7 to 214}	3.3 (3.6)	3.9 (4.2)	
(C)G-T06-1-21 3-21	(C)G-G06-1-21 3-21	3/4		120	0.8 to 7{8.2 to 71.4} 3.5 to 21{35.7 to 214}	5.7 (6.1)	6.2 (6.6)	ISO 5781-AH-08-2-A
(C)G-T10-1-21 3-21	(C)G-G10-1-21 3-21	1 1/4		280	0.8 to 7{8.2 to 71.4} 3.5 to 21{35.7 to 214}	10.0 (11.3)	11.8 (13.1)	ISO 5781-AJ-10-2-A

Weight values in parentheses are for when a check valve is included.
The cracking pressure of the check valve is 0.1MPa{1.0kgf/cm²}

Understanding Model Numbers




Installation Dimension Drawings

G-T**-*-21 (Screw Mounting)

Model No.	Dimensions (mm)					
	A	B	C	D	E	F
G-T03-*-21	146	118.5	52	23	52.5	19
G-T06-*-21	174	148	66.5	27	64	24
G-T10-*-21	203.5	178.5	80.5	28	73	30

Model No.	Dimensions (mm)						
	G	H	J	K	L	M	P
G-T03-*-21	35	70	40	32	63	36	3/8
G-T06-*-21	47.5	95	50	37	73	54	3/4
G-T10-*-21	54	108	68.5	47.5	95	69	1 1/4



• Handling

- ① Provide an independent drain pipe directly to the tank.
- ② When using a remote control valve, connect piping to the reducing valve vent port. Pipe capacity can be a source of vibration. Use of thick iron pipe with an inside diameter of no more than 4mm and a connection length of no more than three meters is recommended.
- ③ Use the following table for specification when a sub plate is required.

Model No.	Pipe Diameter	Weight kg	Applicable Pump Model
MG-03-20	3/8	1.6	(C)G-G03-*-21
MG-03X-20	1/2		
MG-06-20	3/4	3.9	(C)G-G06-*-21
MG-06X-20	1		
MG-10-20	1 1/4	6.7	(C)G-G10-*-21
MG-10X-20	1 1/2		


These sub plates can also be used for pressure control valves.

- ④ The following are the bundled mounting bolts.

Model No.	Bolt Dimensions	Qty	Tightening Torque N·m(kgf·cm)
(C)G-G03-*-21	M10 × 75 ℓ	4	45 to 55 {460 to 560}
(C)G-G06-*-21	M10 × 85 ℓ	4	
(C)G-G10-*-21	M10 × 105 ℓ	6	

Note) For mounting bolts, use 12T or equivalent.


G-G**-*-21 (Gasket Mounting)



Model No.	A	B	C	D	E	F	G	H	J	K	L	M
G-G03-*-21	146	118.5	62	45.1	52.5	19	35	70	60	88	4	60
G-G06-*-21	174	148	82	51.4	64	24	40	80	70	102	4	70
G-G10-*-21	203.5	178.5	102	54	73	30	51	102	92	122	6	92

Note) The orientation of the pressure adjusting handle cannot be change.

CG-T**-*-21 (Screw Mounting)



Model No.	A	B	C	D	E	F	G	H	J	K	L	M	P
CG-T03-*-21	146	118.5	52	23	52.5	19	35	70	40	54	63	36	3/8
CG-T06-*-21	174	148	66.5	27	64	24	47.5	95	50	60	73	54	3/4
CG-T10-*-21	203.5	178.5	80.5	28	73	30	54	108	68.5	80	95	69	1 1/4

Note) After the orientation of the pressure adjusting handle has been changed, also modify the cover alignment surface ring (1B-P6).